



VpCI™ ADDITIVES FOR COATINGS, FLUIDS, ADHESIVES AND PLASTICS

M-530 广州孚润 400-992-6811

Oil Based Corrosion Inhibitor



PRODUCT DESCRIPTION

M-530 is an oil-based package of corrosion inhibitors for hydraulic or lubricating oils. M-530 is a rust preventative product, which provides excellent protection during operating conditions and intermittent operations.

M-530 is very effective for mineral and synthetic oils: naphthenic, iso-paraffinic, PAOs, among others.

FEATURES

- Corrosion protection to ferrous and non-ferrous metals
- Does not contain hazardous barium, chromate, nitrite or phosphate inhibitors
- High flash point
- Low in toxicity and thermally stable, providing long-lasting corrosion inhibition
- Passes through a 5 micron filter
- Can be used in hydraulic applications
- Provides protection in the presence of chlorides
- When added at recommended concentration to hydraulic fluids, does not affect emulsification, pour point or viscosity at low temperatures
- Compatible with most mineral and synthetic oils
- Suitable for both operating and intermittent use conditions

TYPICAL APPLICATION

For hydraulic and lubricating oil systems in intermittent operations, add M-530 to oil at a concentration of 2-5% weight.

METALS PROTECTED

- Carbon steel
- Stainless steel
- Galvanized steel
- Aluminum
- Brass
- Copper
- Cadmium
- Magnesium
- Silver
- Zinc
- Solder
- Tin
- Lead
- Bronze

TYPICAL PROPERTIES

Appearance	Dark brown viscous liquid
Non-volatile Content	95-99%
Density	8.2-8.3 lb/gal (0.98-1.00 kg/l)
pH	6-8 (1% in water)
ASTM D974 TBN	18.22 mg of KOH/g

TYPICAL PROPERTIES

when added at concentration level 2-5% by weight to Hydraulic or Gear oil

ASTM D 1748 (Corrosion protection in Humidity Cabinet)	5+ days
ASTM D 1401 (Water separability of Petroleum and Synthetic Fluids)	<ul style="list-style-type: none"> • Does not cause emulsification • Does not affect oil water separability

PACKAGING AND STORAGE

M-530 is available in 5 gallon (19 liter) plastic pails, 55 gallon (208 liter) metal drums, liquid totes and bulk. M-530 should be sealed before storage. The shelf life is up to 24 months.



FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:

4119 White Bear Parkway, St. Paul, MN 55110 USA
Phone (651) 429-1100, Fax (651) 429-1122
Toll Free (800) 4-CORTEC, E-mail info@corotecvci.com
Internet <http://www.CortecVpCI.com>

printed on recycled paper  10% post consumer
Revised 6/28/06, Cortec Corporation 2005-2006. All rights reserved. Supersedes: 5/3/06.
Diesellall® is a trademark of Castrol.

© 2005-2006, Cortec Corporation. All Rights Reserved. Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited.